

LGR Dehumidifiers

WINMORE LGR dehumidifier is proven workhorse with a market leading 130Pints/day of moisture and 230 Pints/day at saturation. It's designed for even the toughest environments, and ideal for any moisture removal project, This dehumidifier is built-in professional performance and portability, with the rotomolded polyethylene housing, it is more resistant and superior durability.



Model: WMDHLGR130



Model	WMDHLGR130	
Dehumidify Capacity	100L/Day(30°C,RH80%)	130Pints/Day (80°F,60 %RH)@AHAM
Power Supply	AC220-240V/50Hz	AC110V-120V/60Hz
Power Current	5.73A (30°C,RH80%)	8.3A (80 °F , 60 %)
Power Consumption	1288W (30°C,RH80%)	945W (80 °F , 60 %)
Refrigerant	R410A	R410A
Body Size(inch)	85*50.8*50.8CM	33.5*20*20Inch
Net Weight	50KG	110lbs
Loading Quantity(20'/40'HQ)	54/114pcs	54/114pcs

Product features

- Hot gas valve system enable better capacity in low temp situation
- Three-minute automatic delay protection of the compressor
- Low amps and low power consumption, safe and energy saving
- Back air outlet , can connect air duct; Draw and push type air filter , more convenient
- With hoppy brand water pump and tough wheels,work stably and low failure rate
- Continuous drainage outlet assure machine drain normally in case of water pump break down

Model: WMDHLGR90P



Model	WMDHLGR90P	
Dehumidify Capacity	73L/Day(30°C,RH80%)	93pints/ Day (80°F, 60%RH)@AHAM
Power Supply	AC220-240V/50Hz	AC110V-120V/60Hz
Power Current	4.2A (30°C,RH80%)	7.0A (80°F, 60%RH)
Power Consumption	928W (30°C,RH80%)	735W (80°F, 60%RH)
Refrigerant	R410A	R410A
Body Size(inch)	54.8*48.3*80.8CM	21.6*19*31.8Inch
Net Weight	40.2KG	93lbs
Loading Quantity(20'/40'HQ)	114/228pcs	114/228pcs

Product features

- Hot gas valve system enable better capacity in low temp situation
- Three-minute automatic delay protection of the compressor
- Low amps and low power consumption, safe and energy saving
- Back air outlet , can connect air duct; Draw and push type air filter , more convenient
- With hoppy brand water pump and tough wheels,work stably and low failure rate
- Continuous drainage outlet assure machine drain normally in case of water pump break down

Model: WMDHLGR90C



Model	WMDHLGR90C	
Dehumidify Capacity	70L/Day(30°C,RH80%)	93pints/ Day (80°F, 60%RH)@AHAM
Power Supply	AC220-240V/50Hz	AC110V-120V/60Hz
Power Current	4.2A (30°C,RH80%)	7.0A (80°F, 60%RH)
Power Consumption	986W (30°C,RH80%)	735W (80°F, 60%RH)
Refrigerant	R410A	R410A
Body Size(inch)	54.8*48.3*80.8CM	21.6*19*31.8Inch
Net Weight	40.2KG	93lbs
Loading Quantity(20'/40'HQ)	114/228pcs	114/228pcs

Product features

- Hot gas valve system enable better capacity in low temp situation
- Three-minute automatic delay protection of the compressor
- Low amps and low power consumption, safe and energy saving
- Back air outlet , can connect air duct; Draw and push type air filter , more convenient
- With hoppy brand water pump and tough wheels,work stably and low failure rate
- Continuous drainage outlet assure machine drain normally in case of water pump break down



CONTACT WITH US

WINMORE GROUP (CHINA) CO.,LTD | XIAMEN WINMORE TRADE CO.,LTD

Add: 2203-2, Taidi Haixi Center Building B, Haicang District, Xiamen City, China

W: www.winmorehvac.com E: mathew@winmorehvac.com Tel: 0086-592-6050171